

# C-PINS METROLOGY WORK

**BUOY SET SOLUTIONS** 



Copyright © 2016 ZUPT, LLC Confidential The data contained on these pages does not meet the definition of "Technical Data" under 22 CFR 120.10

- C-PINS aligns to known subsea location (nearby structure)
  (Will require ability to stab into something receptacle)
- Needs a single point to align to (accuracy unimportant : ~30m)

- All buoys will be placed relative to the alignment position – or manifold/PLET/PLEM slot



If the nearby structure with receptacle is over ~50 meters away Zupt will deploy an auxiliary hub closer to buoy locations

Auxiliary Hub (Aux Hub) is a receptacle on a parking frame

The Aux Hub will be tied into the known coordinates of the subsea structure nearby. The Aux Hub will be used to reference buoy placement and keep C-PINS drift minimal.

Two loops to Aux Hubs gives us <20cm relative (20 mins)



Aligned C-PINS can navigate to place a buoy frame

Alternatively buoys can be placed

one by one



Real time visual map of buoy set targets / frames / ROV



#### Data QC

#### Buoy location accuracy in real time

Buoy	Buoy Set Processing								
	Buoy Results Error to								
Buoy	Ref.	Name		Northing	Easting	Range	Bearing	Target	1
1	×	Align-Pos		3315064.429	257081.592	0.000	180.0	0.000	- A
2		<b>Buoy-Frame</b>		3315063.498	257082.668	1.423	310.9	1.423	
3		Buoy#1_1		???	???	???	???	???	
4		Buoy#1_2		???	???	???	???	???	
5	Г.	Buoy#1_3		???	???	???	???	???	
6	Г.	Buoy#1_4		???	???	???	???	???	
				ن بالدين (				Maura	-
2	Individual Loops Mo							Move	4
	Ena	Misclosur	e	Northing	Easting	Hange	Bearing	Uffset	
1		0.000		0.000	0.000	0.000	0.0	0.000, 0.000	
4		0.000		0.000	0.000	0.000	0.0	0.000, 0.000	
3		0.000		0.000	0.000	0.000	0.0		
4		0.000		0.000	0.000	0.000	0.0		-
<u>c</u>		0.000		0.000	0.000	0.000	0.0		-
7		0.000		0.000	0.000	0.000	0.0		-
8		0.000		0.000	0.000	0.000	0.0		-
9		0.000		0.000	0.000	0.000	0.0		-
10		0.000		0.000	0.000	0.000	0.0		-
	Mashina Ea								
	N	orthing	E	asting					
FIX		0.000		000					
		0.000		0.000					
		0.000	_ L	).000					

#### TIMES FOR INERTIAL BUOY SET

Align	45 mins
Aux Hub placement – if needed	<30mins
Frame Placement (if buoy pattern needed)	40 mins
Buoy Placement to Frame	60 mins

Total time for well buoy set

<4 hours

Buoy relative accuracy to known point <20cm. Buoy to buoy relative accuracy - <5cm.

No array needed, no transponder frames, no array calibration and add on.

Copyright © 2016 ZUPT Confidential The data contained on these pages does not meet the definition of "Technical Data" under 22 CFR 120.10